


Amendment to the Abstract:

The Abstract has been amended. A revised Abstract is attached.

ABSTRACT

A built-in heating cooker which features both good cooling performance and effective countermeasures against spilled liquids by preventing ingress of water into the cooker body with a simple ventilation structure. This built-in cooker comprises a top plate (11) where a pot and the like are placed, a support (12) for supporting the top plate (11) from underneath, a top frame (15) covering the edge of the top plate (11) and a frame (16) constituting the cooker body. The Ssupport (12) has a cooker-supporting face (17) for supporting the cooker, and this is positioned outside of the top plate-supporting face (13). A First-first opening (20) is provided on at least one side wall provided between the top plate-supporting face (13) and the cooker-supporting face (17). A Second-second opening (21) is provided on a frame (15) in a position corresponding to the first opening (20).

Respectfully submitted,


Lawrence E. Ashery, Reg. No. 34,515
Attorney for Applicants

LEA/fp

Attachments: Figure 11 (1 sheet)

Dated: May 17, 2005

P.O. Box 980
Valley Forge, PA 19482-0980
(610) 407-0700

The Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. **18-0350** of any fees associated with this communication.

EXPRESS MAIL: Mailing Label No.: EV 447 719 498 US
Date of Deposit: May 17, 2005

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.


KATHLEEN LIBBY

ABSTRACT

A built-in heating cooker which features both good cooling performance and effective countermeasures against spilled liquids by preventing ingress of water into the cooker body with a simple ventilation structure. This built-in cooker comprises a top plate where a pot and the like are placed, a support for supporting the top plate from underneath, a top frame covering the edge of the top plate and a frame constituting the cooker body. The support has a cooker-supporting face for supporting the cooker, and this is positioned outside of the top plate-supporting face. A first opening is provided on at least one side wall provided between the top plate-supporting face and the cooker-supporting face. A second opening is provided on a frame in a position corresponding to the first opening.